

FEELING LIGHT
LIFE





RE'S R&D. AND THERE'S LUMCA R&D.

With an innovation-driven culture and commitment to high performance, we ensure that the quality of our products surpasses industry standards. From our designs to the materials we use to our manufacturing processes, Lumca provides crave-worthy lighting products for large-scale projects and prestigious clients in North and Central America.

The future of outdoor lighting
comes from the inside.

Meet Lumca's first Urban-Cozy light, LIO. Sleek and stylish, its design pays tribute to the lights that transform our homes into oases. With LIO, the high-quality and aesthetic narrative of interior light fixtures is now brought to public spaces—with the performance and robustness operators require.





Outdoor lighting never
had this much quality.

UP TO 15 000 LUMENS LIO-L (LARGE)

UP TO 125 LUMENS / WATT

DISTRIBUTIONS: I,II,III,IV,V

CCT: 3000K AND 4000K

CRI: 70-80

DARK SKY COMPLIANT

CSA

IP66



LIO-L
LF9 CF80 36

OPTIONS

HSS

HOUSE SIDE SHIELD (INTERNAL)

BTP

BUTTON TYPE PHOTOCELL

PER

TWIST LOCK PHOTOCELL
RECEPTACLE (ANSI C136.41)

RCD-DOF

INTERNAL DIMONOFF LIGHT CONTROL SYSTEM
C/W ANTENNA (SOFTWARE NOT INCLUDED)

TRP7

7 PINS TWIST LOCK PHOTOCELL RECEPTACLE
(ANSI C136.41) C/W SHORTING CAP

TRP

7 PINS TWIST LOCK PHOTOCELL RECEPTACLE
(ANSI C136.41) C/W PHOTOCELL



AVAILABLE DIMENSION OPTIONS

LIO-S (SMALL)




UP TO 10 000 LUMENS

LIO-M (MEDIUM)

UP TO 15 000 LUMENS

LIO-L (LARGE)

UP TO 15 000 LUMENS






COSMO

PR8475
(4 ARMS)

PR8275
(2 ARMS)



Say hello to Cosmo,
a revamped take
on a popular classic
in urban lighting.

Cosmo pays tribute to lanterns of by-gone eras with a modern twist. Add elegance and prestige to any city landscape.

UP TO 20 000 LUMENS

UP TO 110 LUMENS / WATT

DISTRIBUTIONS: I,II,III,IV,V

CCT: 3000K AND 4000K

CRI: 70-80

DARK SKY COMPLIANT

IP66

CSA

OPTIONS

HSS

HOUSE SIDE SHIELD (INTERNAL)

BTP

BUTTON TYPE PHOTOCELL

PER

TWIST LOCK PHOTOCELL RECEPTACLE (ANSI C136.41)

RCD-DOF

INTERNAL DIMONOFF LIGHT CONTROL SYSTEM
C/W ANTENNA (SOFTWARE NOT INCLUDED)

TRP7

7 PINS TWIST LOCK PHOTOCELL RECEPTACLE
(ANSI C136.41) C/W SHORTING CAP

TRP

7 PINS TWIST LOCK PHOTOCELL RECEPTACLE
(ANSI C136.41) C/W PHOTOCELL

CITII

Never compromise
on city style.

Meet Citii, a sleek new line of LED lights
that blend in harmoniously in any
contemporary urban design. A touch
of muted luxury that goes a long way.



PR8476
(4 ARMS)



PR8276
(2 ARMS)

UP TO 20 000 LUMENS
UP TO 110 LUMENS / WATT
DISTRIBUTIONS: I,II,III,IV,V
CCT: 3000K AND 4000K
CRI: 70-80
DARK SKY COMPLIANT
IP66
CSA

OPTIONS

HSS
HOUSE SIDE SHIELD (INTERNAL)

BTP
BUTTON TYPE PHOTOCELL

PER
TWIST LOCK PHOTOCELL
RECEPTACLE (ANSI C136.41)

RCD-DOF
INTERNAL DIMONOFF LIGHT CONTROL SYSTEM
C/W ANTENNA (SOFTWARE NOT INCLUDED)

TRP7
7 PINS TWIST LOCK PHOTOCELL RECEPTACLE
(ANSI C136.41) C/W SHORTING CAP

TRP
7 PINS TWIST LOCK PHOTOCELL RECEPTACLE
(ANSI C136.41) C/W PHOTOCELL



N O N - L U M

Silver

RA-S

Black

RA-B

C O L O R A



INOUS

Orange

RA-O

CENTS

Red

RA-R

Ø 4"

WB24-4



Ø 5"

WB24-5



Bases



COSMO



C096



C072



C042



CitiII



CT96



CT72



CT42

AESTHETIC POLES AND BASES

Bollards

UP TO 4 000 LUMENS

UP TO 100 LUMENS / WATT

DISTRIBUTIONS: I,II,III,IV,V

VOLTAGE: 120, 208, 240, 277, 347, 480

WATTAGE LED: 20-40W

DARK SKY COMPLIANT

IP66

OPTIONS

HSS

HOUSE SIDE SHIELD (INTERNAL)

BTP

BUTTON TYPE PHOTOCELL






AURA

Aura: Outdoor LED lighting that masters each moment.

Aura is a new generation of outdoor lighting solutions for cities that defies convention. Imagine being able to take advantage of the design flexibility, energy savings and lifespan of LED lights—all while offering the warm ambience of traditional lighting. That is the breakthrough with AURA. Never compromise on look—or performance.





UP TO 10 000 LUMENS
UP TO 110 LUMENS / WATT
DISTRIBUTIONS: I,II,III,IV,V
AND 90-DEGREE BEAM ANGLE
CCT: 3000K AND 4000K
CRI:80
IP66
CSA

OPTIONS

HSS:
HOUSE SIDE SHIELD (INTERNAL)

RCD-DOF:
INTERNAL DIMONOFF LIGHT
CONTROL SYSTEM C/W ANTENNA
(SOFTWARE NOT INCLUDED)

MOD-DOF:
INTERNAL DIMONOFF RGBW LIGHT
CONTROL SYSTEM C/W ANTENNA

TRP7:
7 PINS TWIST LOCK PHOTOCELL
RECEPTACLE (ANSI C136.41)
C/W SHORTING CAP

Configurations

CURVED
AU-C6TC
AU-C8TC



STRAIGHT
AU-C6TS
AU-C8TS



CLASSIC
AU-C6
AU-C8



STANDARD POLE

AVAILABLE WITH THESE CONFIGURATIONS:

-  Ø 4" AU-C6TC
AU-C6TS
-  Ø 6" AU-C8TC
AU-C8TS
AU-C6
-  Ø 8" AU-C8




RAIL POLE

AVAILABLE WITH THESE CONFIGURATIONS:

-  Ø 6" AU-C8TC
AU-C8TS
AU-C6
-  Ø 8" AU-C8

Ø 6"

Lens diameter




Ø 8"

48"



36"



24"



RGBW

UP TO 3000 LUMENS *

UP TO 100 LUMENS / WATT *

DISTRIBUTIONS: V

3000K and 4000K

CRI: 80

IP66

CSA

* Performance based on white spectrum only; CCT 3000K and 4000K



Multiple possibilities. Limitless creativity.

Bases



WRAP-AROUND BASE COVER



BURIED BASE

Bollards

UP TO 6 000 LUMENS

UP TO 110 LUMENS / WATT

DISTRIBUTIONS: I,II,III,IV,V

AND 90-DEGREE BEAM ANGLE

CCT: 3000K AND 4000K

CRI: 80

IP66

CSA

OPTIONS

RCD-DOF:

INTERNAL DIMONOFF LIGHT
CONTROL SYSTEM C/W ANTENNA
(SOFTWARE NOT INCLUDED)

MOD-DOF:

INTERNAL DIMONOFF RGBW LIGHT
CONTROL SYSTEM C/W ANTENNA



HEIGHTS
40"



HEIGHTS
42"

AU-B6
AU-B8

AU-B6-WB
AU-B8-WB

AU-BLF6
AU-BLF8

AU-BLF6-WB
AU-BLF8-WB



