

PENDANT

Mounting arms

Technical informations

Date

City / Location

Project name

Type

Qty



clamp height: 8" [203mm]

CF4

EPA 1.53 ft²



M1-CF4


EPA 0.94 ft²



clamp height: 8" [203mm]

CF5

EPA 1.31 ft²



clamps height: 20" [508mm]

CF48

EPA 1.76 ft²

CONSTRUCTION

All cast aluminium pieces are #356 alloy, free of any porosity or foreign material. The minimum wall thickness of all castings is 0.188" [4.75mm]. Extruded aluminium parts are #C6005-T5 alloy.


All hardware is in stainless steel

FINISH

Powder coating minimum thickness 100 microns, ASTM D2247 5000 hours salt spray test. All metallic parts are pre-treated using an environmentally friendly organic phosphating technology (PLAFORIZATION) before a polyester powder coating is electrostatically applied. The finish is of 100 microns minimal thickness and meets the ASTM B117 regulation related to salt spray and the ASTM D2247 regulation related to the resistance of the finishes exposed to a 100% relative humidity. RAL and Custom colour matches available.

Ordering example: M1A-CFxx BK

Mounting Configuration




Arm

Color




*M1 Configuration available only with CF4 & CF5 brackets


Mounting Overview




Pole mount (M1A & M2)
Clamp style




Pole mount (PM)
Mechanical



Rail pole mount (LF)
Mechanical



Wall mount (MA)
Mechanical
(Hardware not included)



Height depends on arm model (average of 15")

Wood pole mount (WA)
C/W liquid tight connector

Lumca reserves the right to modify the elements on this technical data sheet without prior notice.